



Alarm Status Table



Description
<p>The alarm status table displays the current state of the alarm system. It can be configured to show active, unacknowledged, cleared, and acknowledged alarms. By default it shows all non-cleared/non-ack'ed alarms.</p> <p>Acknowledgement is handled by selecting (checking) alarms and pressing the "Acknowledge" button. If any of the selected alarms require acknowledgement notes, then a small text area will be presented in which the operator must add notes to the acknowledgement.</p> <p>Shelving is supported by pressing the "Shelve" button when an alarm is selected. This will temporarily remove the alarm from the entire alarm system (not just the local client). When the time is up, if the alarm is still active, it will pop back into the alarm system. The times shown to the user are customizable by editing the values inside the "Shelving Times" dataset property. The alarms that have been shelved can be un-shelved by pushing the shelf management button in the lower right-hand side of the component.</p> <p>If a more simplified alarm status table is needed, many of the features of the status table can be removed, for example, the header, footer, and multi-selection checkboxes. If a very short alarm status table is needed, turn on the "Marquee Mode" option, which will automatically scroll through any alarms if there is not enough vertical space to show all of them at once.</p> <p>To change the columns that are displayed, the order of the columns, and/or the column width, put the Designer into preview mode. Then right-click on the table header to show/hide columns. Click and drag to re-order columns, and drag the margins of the columns to resize their width. No further action is necessary - the column configuration will remain in place after the window is saved.</p> <p>For alarms that originate from Tags that have Tag history turned on, users can see an automatic ad-hoc chart for the value of the source Tag by pressing the chart button.</p>
<p> An Example of configuring the Alarm Status Table can be found on the Alarm Status Table Component page.</p>

Properties			
Name	Description	Property Type	Scripting
Antialias	Draw the component with antialias on. This makes text look smoother	boolean	.antialias
Border	The border surrounding this component. NOTE that the border is unaffected by rotation.	Border	.border
Chart Resolution	The resolution for the ad-hoc tag historian chart.	int	.chartResolution
Data Quality	The data quality code for any tag bindings on this component.	int	.dataQuality

Date Format	A date format pattern used to format dates in the table. If blank, the default format for the locale is used.	String	.dateFormat
Display Path Filter	Filter alarms by alarm display path, falling back to the source path if a custom display path isn't set. Specify multiple paths by separating them with commas. This field supports the wildcard "*" to match any number of characters.	String	.displayPathFilter
Duration Format	<div style="border: 1px solid black; background-color: #fff9c4; padding: 5px; text-align: center;"> <p>This feature is new in Ignition version 7.9.12 Click here to check out the other new features</p> </div> <p>Format for the time units on the Active Duration column: Long, Short, Compact, and Abbreviated.</p>		
Enabled	If disabled, a component cannot be used.	boolean	.componentEnabled
Flash Interval	The time interval to use for flashing row styles.	int	.flashInterval
Journal Name	The name of the alarm journal to query for the chart's annotations. Leave this blank to automatically pick the journal if there is only one.	String	.alarmJournalName
Marquee Mode	Turn the table into a scrolling marquee	boolean	.marqueeMode
Min Priority	The minimum priority alarm to be displayed by this table.	int	.minPriority
Multi Select	Allow multi select. Will show/hide the checkbox column.	boolean	.multiSelect
Name	The name of this component.	String	.name
Notes Area Border	The border surrounding the notes area.	Border	.notesAreaBorder
Notes Area Font	The font for the notes area.	Font	.notesAreaFont
Notes Area Location	The location of the notes display area	int	.notesAreaLocation
Notes Area Size	The size of the notes area, in pixels.	int	.notesAreaSize
Number Format	A number format string to control the format of the value column.	String	.numberFormat
Refresh Rate	The rate at which this table will poll changes to the alarm status, in milliseconds.	long	.refreshRate
Row Height	The height, in pixels, for each row of the table.	int	.rowHeight
Row Styles	A dataset containing the different styles configured for different alarm states.	Dataset	.rowStyles

Scroll Delay	The time (in mSec) to wait between performing each step in a scroll	int	.scrollDelay
Selected Alarms	A dataset containing each selected alarm. (Read-only)	Dataset	.selectedAlarms
Selection Color	The color of the selection border	Color	.selectionColor
Selection Thickness	The size of the selection border	int	.selectionThickness
Shelving Times	This dataset holds the times that are suggested when shelving an alarm. Allowable units are "second", "minute", or "hour".	Dataset	.shelvingTimes
Show Ack Button	Show the acknowledge button on the footer panel.	boolean	.showAck
Show Active and Acked	Show alarms that are active and acknowledged.	boolean	.activeAndAked
Show Active and Unacked	Show alarms that are active and unacknowledged.	boolean	.activeAndUnacked
Show Chart Button	Show the chart button on the footer panel.	boolean	.showChart
Show Clear and Aked	Show alarms that are cleared and acknowledged.	boolean	.clearAndAked
Show Clear and Unacked	Show alarms that are cleared and unacknowledged.	boolean	.clearAndUnacked
Show Details Button	Show the view details button on the footer panel.	boolean	.showDetails
Show Footer	Show a footer with acknowledge and shelf functions below the alarms.	boolean	.showFooterPanel
Show Header Popup	Toggles the table header's built-in column selection popup menu.	boolean	.showTableHeaderPopup
Show Manage Shelf Button	Show the manage shelf button on the footer panel.	boolean	.showManageShelf
Show Shelf Button	Show the shelve button on the footer panel.	boolean	.showShelve

Show Table Header	Toggles visibility of the table's header.	boolean	.showTableHeader
Sort Oldest First	Sort times by oldest first.	boolean	.sortOldestFirst
Sort Order	The default sort order for alarms in the status table.	int	.sortOrder
Source Filter	Filter alarms by alarm source path. Specify multiple paths by separating them with commas. This field supports the wildcard "*" to match any number of characters.	String	.sourceFilter
Stay Delay	The time (in mSec) to wait between scrolls	int	.stayDelay
Table Background	The background of the alarm table.	Color	.tableBackground
Table Header Font	The font for the table header.	Font	.tableHeaderFont
Touchscreen Mode	Controls when this input component responds if touchscreen mode is enabled.	int	.touchscreenMode
Visible	If disabled, the component will be hidden.	boolean	.visible

Scripting

Scripting Functions

- Description

This specialized print function will paginate the table onto multiple pages. This function accepts keyword-style invocation.

- Keyword Args

boolean fitWidth - If true, the table's width will be stretched to fit across one page's width. Rows will still paginate normally. If false, the table will paginate columns onto extra pages. (default = true) [optional]

string headerFormat - A string to use as the table's page header. The substring "{0}" will be replaced with the current page number. (default = None) [optional]

string footerFormat - A string to use as the table's page footer. The substring "{0}" will be replaced with the current page number. (default = "Page {0}") [optional]

boolean showDialog - Whether or not the print dialog should be shown to the user. Default is true. [optional]

boolean landscape - Used to specify portrait (0) or landscape (1) mode. Default is portrait (0). [optional]

- Return

Boolean - True if the print job was successful.

- Scope

Client

This feature is new in Ignition version **7.9.7**
[Click here](#) to check out the other new features

- Description

Returns a dataset of the alarms currently displayed in the Alarm Status Table component. The columns will be: EventId, Source, DisplayPath, EventTime, State, and Priority.

- Keyword Args

None

- Return

Dataset - A dataset of alarms.

- Scope

Client

Extension Functions

- Description

Returns a popup menu that will be displayed when the user triggers a popup menu (right click) in the table. Use *system.gui.PopupMenu()* to create the popup menu.

- Parameters

Component self- A reference to the component that is invoking this function.

List selectedAlarmEvents - The alarm events selected on the Alarm Status Table. For an individual alarm Event, call *alarmEvent.get('propertyName')* to inspect. Common properties: 'name', 'source', 'priority'.

- Return

Object - the popup menu.

- Scope

Client

- Description

Called for each event loaded into the alarm status table. Return false to hide this event from the table. This code is executed in a background thread.

- Parameters

Component self- A reference to the component that is invoking this function.

Alarm Event alarmEvent - The alarm event itself. Call *alarmEvent.get('propertyName')* to inspect. Common properties: 'name', 'source', 'priority'.

- Return

Boolean- Returns true or false for every alarm event in the table. True will show the alarm. False will not show the alarm.

- Scope

Client

- Description

Returns a boolean that represents whether the selected alarm can be acknowledged

- Parameters

Component self- A reference to the component that is invoking this function.

List selectedAlarmEvents - The alarm events selected on the Alarm Status Table. For an individual alarmEvent, call *alarmEvent.get('propertyName')* to inspect. Common properties: 'name', 'source', 'priority'.

- Return

Boolean- Returns true or false for every alarm event in the table.

- Scope

Client

- Description

Returns a boolean that represents whether the selected alarm can be shelved.

- Parameters

Component self- A reference to the component that is invoking this function.

List selectedAlarmEvents - The alarm events selected on the Alarm Status Table. For an individual alarmEvent, call alarmEvent.get('propertyName') to inspect. Common properties: 'name', 'source', 'priority'.

- Return

Boolean- Returns true or false for every alarm event in the table.

- Scope

Client

- Description

Called when an alarm is double-clicked on to provide custom functionality.

- Parameters

Component self- A reference to the component that is invoking this function.

Alarm Event alarmEvent - The alarm event that was double clicked. For an individual alarmEvent, call alarmEvent.get('propertyName') to inspect. Common properties: 'name', 'source', 'priority'.

- Return

Nothing

- Scope

Client

- Description

Called when the Acknowledge button is pressed; the script runs before the ack happens. Return False to abort the acknowledgement, return True to continue as normal.

- Parameters

Component self- A reference to the component that is invoking this function.

List alarms - A list of the alarms to be acknowledged.

- Return

Boolean- Returns true or false for every alarm event that is selected.

- Scope

Client

Event Handlers

Fires whenever a bindable property of the source component changes. This works for standard and custom (dynamic) properties.

. source	The component that fired this event
. newValue	The new value that this property changed to.
. oldValue	The value that this property was before it changed. Note that not all components include an accurate oldValue in their events.
. propertyName	The name of the property that changed. NOTE: remember to always filter out these events for the property that you are looking for! Components often have many properties that change.

Customizers

Alarm Row Styles

The Alarm Status Table has a customizer.

- Component Customizers

Examples

Code Snippet

```
#The following code is an example of the filter alarm expression function.  
#The function results in advanced filtering for the alarm table.  
#In this example the alarm table will only show alarms with a name that matches the value of  
the "AreaName" property located on the container the Alarm Status Table resides in.
```

```
name = self.parent.AreaName  
if name == alarmEvent.get('name'):  
    return True  
else:  
    return False
```

Gallery

Alarm Status Table with a Single Alarm

<input type="checkbox"/>	Active Time	Display Path	Current State	Priority
<input type="checkbox"/>	1/20/15 8:26 AM	London	Active, Unacknowledged	Low

Acknowledge Shelf